



## North Coast Conduit Micro Duct Riser

### Dimensions

OD/ID	Outside Diameter		Walls		Inside Diameter	LBS/FT	Bend Radius	
	Min	Max	Min	Max			Supported	Unsupported
8.5/6mm	0.331	0.339	.045	.053	0.232	0.02	3 in.	6 in.
10/8mm	0.39	0.398	0.035	0.043	0.315	0.02	4 in.	8 in.
12/10mm	0.468	0.476	0.035	0.043	0.394	0.024	5 in.	10 in.
12.7/10mm	0.496	0.504	0.049	0.057	0.394	0.034	5 in.	10 in.
16/12mm	0.626	0.634	0.074	0.082	0.462	0.062	6 in.	12 in.
16/13mm	0.626	0.634	0.055	0.063	0.512	0.049	6 in.	12 in.
18/14mm	0.705	0.713	0.075	0.083	0.551	0.072	7 in.	14 in.

**Applicable Standards:** Production Specifications and UL 2024  
*(ETL Listed conforming to UL 2024)*

### General Specifications:

**Color:** Natural – (other colors and striping options available upon request)

**Conduit Type:** Smooth O.D. / Ribbed I.D.

**Nominal Density:** 0.947 g/cm<sup>3</sup>

**Material Type:** HDPE (base) + Flame Retardant Additive

**Options:** Pre-Lubricated: Silicone lubricant GE #SF96-350 or equivalent

*\*I.D. is measured at peak of rib*

*\* wall thickness is measured in valley between ribs*

www.northcoastconduit.com

